

**In the claims:**

Please amend claims 1, 7 and 13 to read as follows:

1. (Currently Amended) A method for controlling display of content signals, the method comprises the steps of:

a) receiving a content signal in a graphics controller, the content signal [[that]]  
includes at least one of video, audio, and text content and at least one associated content control indicator;

b) ~~passing the content signal through a scrambler without scrambling the content signal;~~  
e) comparing the at least one associated content control indicator with at least one content control setting;

c) receiving the content signal in a tuner;

when the at least one associated content control indicator compares unfavorably to the at least one content control setting:

d) generating a scramble control signal;

e) providing the scramble control signal to at least one of a video scrambler and an audio scrambler;

~~using the scrambler;~~ f) scrambling at least a portion of the at least one of video, audio, and text content to produce scrambled content; and

eg) providing the scrambled content to a content rendering device.

2. (Original) The method of claim 1 further comprises:

scrambling at least a portion of the audio content to produce scrambled audio content,

wherein the content signal includes the audio content; and

providing the scrambled audio content to an audio rendering device.

3. (Original) The method of claim 2 further comprises attenuating the at least a portion of the audio content to produce the scrambled audio content.

4. (Previously presented) The method of claim 1 further comprises:  
scrambling the text content to produce scrambled text content, wherein the content signal includes the text content; and  
providing the scrambled text content to a display.

5. (Original) The method of claim 1 further comprises:  
interpreting the at least one associated content control indicator to determine copy restriction status; and  
when copy restriction is enabled, preventing copying of the content signal.

6. (Original) The method of claim 1 further comprises:  
providing an audio scrambling signal to an audio processing module when the at least one associated content control indicator compares unfavorably to the at least one content control setting.

7. (Currently Amended) A content controller comprises:  
a processing module; and  
memory operably coupled to the processing module, wherein the memory stores operational instructions that cause the processing module to (a) receive a content signal in a graphics control module, the content signal ~~[[that]]~~ includes at least one of video, audio, and text content and at least one associated content control indicator; (b) ~~passing the content signal through a scrambler without scrambling the content signal;~~ (c) compare the at least one

associated content control indicator with at least one content control setting (c) receive the content signal in a tuning module;

when the at least one associated content control indicator compares unfavorably to the at least one content control setting: (d) generate a scramble control signal; ~~(e) using the scrambler,~~ scramble at least a portion of the at least one of video, audio, and text content to produce scrambled content; and (e) provide the scrambled content to a content rendering device.

8. (Original) The content controller of claim 7, wherein the memory further comprises operational instructions that cause the processing module to:

scramble at least a portion of the audio content to produce scrambled audio content, wherein the content signal includes the audio content; and

provide the scrambled audio content to an audio rendering device.

9. (Original) The content controller of claim 8, wherein the memory further comprises operational instructions that cause the processing module to attenuate the at least a portion of the audio content to produce the scrambled audio content.

10. (Original) The content controller of claim 7, wherein the memory further comprises operational instructions that cause the processing module to:

scramble at least a portion of the text content to produce scrambled text content, wherein the content signal includes the text content; and

provide the scrambled text content to the display.

11. (Original) The content controller of claim 7, wherein the memory further comprises operational instructions that cause the processing module to:

interpret the at least one associated content control indicator to determine copy restriction status; and

when copy restriction is enabled, preventing copying of the content signal.

12. (Original) The content controller of claim 7, wherein the memory further comprises operational instructions that cause the processing module to:

provide an audio scrambling signal to an audio processing module when the at least one associated content control indicator compares unfavorably to the at least one content control setting.

13. (Currently Amended) A video device comprises:

a tuner operably coupled to receive a content signal and to produce, therefrom, a digitized content signal;

a video decoder operably coupled to received the digitized content signal and to produce, therefrom, decoded video;

a graphics controller operably coupled to receive the decoded video and to provide, therefrom, a video output, wherein the graphics controller includes:

a processing module; and

memory operably coupled to the processing module, wherein the memory stores operational instructions that cause the processing module to (a) monitor at least one of the content signal, the digitized content signal, the decoded video, and the video output, wherein the at least one of the content signal, the digitized content signal, the decoded video, and the video output includes video content and at least one associated content control indicator; (b) ~~passing the content signal through a scrambler without scrambling the content signal;~~ (c) compare the at least one associated content control indicator with at least one content control setting;

when the at least one associated content control indicator compares unfavorably to the at least one content control setting: ~~(d)~~ (c) generating a scramble control signal; (d)

providing the scramble control signal to at least one of a video scrambler and an audio scrambler;  
(e) using the scrambler, control scrambling of at least a portion of the digitized content signal or  
the decoded video to produce scrambled video content; and ~~(e)~~(f) provide the scrambled video  
content as the video output.

14. (Original) The video device of claim 13 further comprises an audio decoder operably coupled to the tuner, wherein the audio decoder decodes digital audio of the content signal to produce decoded audio, and wherein the memory further includes operational instructions that cause the processing module to:

control scrambling of at least a portion of the digital audio or the decoded audio to produce scrambled audio content, such that the scrambled audio content is provided to an audio rendering device.

15. (Original) The video device of claim 14, wherein the memory further comprises operational instructions that cause the processing module to control attenuation of the at least a portion of the digital audio or the decoded audio to produce the scrambled audio content.

16. (Original) The video device of claim 15 further comprises at least one of: a scramble module and an attenuation module operably coupled to the audio decoder.

17. (Original) The video device of claim 13, wherein the memory further comprises operational instructions that cause the processing module to:

control scrambling at least a portion of closed captioned content to produce scrambled closed captioned content, wherein the content signal includes the closed captioned content; and  
provide the scrambled closed captioned content as part of the video output.

18. (Original) The video device of claim 13, wherein the memory further comprises operational instructions that cause the processing module to:

interpret the at least one associated content control indicator to determine copy restriction status; and

when copy restriction is enabled, preventing copying of the video content.

19. (Original) The video device of claim 13, wherein the memory further comprises operational instructions that cause the processing module to:

provide an audio scrambling signal to an audio processing module when the at least one associated content control indicator compares unfavorably to the at least one content control setting.

20. (Original) The video device of claim 13 further comprises at least one of: a display and a recorder, wherein the display and the recorder are operably coupled to receive the video output.

21. (Original) The video device of claim 13 further comprises a scramble module operably coupled to scramble, when enabled, the at least a portion of the digitized content signal or the decoded video.

22. (Original) The video device of claim 13, wherein the graphics control further comprises a scramble module operably coupled to scramble, when enabled, the at least a portion of the digitized content signal or the decoded video.